



**HIGH PERFORMANCE LUBRICANT** DESIGNED FOR TURBOCHARGED OR NATURALLY ASPIRATED ENGINES USED IN **AGRICULTURAL AND INDUSTRIAL MACHINES.**

## SPECIFICATIONS AND APPROVALS

International specifications

ACEA E7

API CI-4/CH-4/SL

The product is approved for KUBOTA engines.

The formulation is approved according to:

- ✓ CUMMINS CES 20078
- ✓ VOLVO VDS-3
- ✓ RENAULT-VI RLD-2

The product is also suitable for the following engines:

- ✓ MAN
- ✓ MERCEDES-BENZ
- ✓ DEUTZ...

## APPLICATIONS

KUBOTA ENGINE OIL POWER 15W-40 is suitable for all agricultural Diesel engines, turbocharged or naturally aspirated, compliant to EUROPE Stage IIIa or US EPA Tier 3 standard, not equipped with Diesel Particulate Filter.

This lubricant can be used in engines compliant with previous standards.

KUBOTA ENGINE OIL POWER 15W-40 can also be used in small gasoline engines of service vehicles.

## PERFORMANCES AND CUSTOMER BENEFITS

KUBOTA ENGINE OIL POWER 15W-40 contains **good viscosity stability in service**, guaranteeing effective engine lubrication in all conditions.

Thanks to its **outstanding anti-wear properties**, KUBOTA ENGINE OIL POWER 15W-40 provides proper lubrication with longer oil drain intervals.

Piston cleanliness performance affords effective protection against cylinder liner polishing for better engine efficiency.

## PHYSICAL AND CHEMICAL CHARACTERISTICS\*

KUBOTA ENGINE OIL POWER 15W-40		METHOD	VALUE
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	98.7
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	13.4
Viscosity Index	-	ASTM D2270	136
Pour Point	°C	ASTM D97	-30
T.B.N	mg KOH/g	ASTM D2896	11

\* The features mentioned above are average values obtained with some variability in production and do not constitute a specification