



MULTIPURPOSE EXTREME PRESSURE LITHIUM/CALCIUM GREASE.

SPECIFICATIONS AND APPROVALS

International specifications

ISO 6743-9 : L-XBCEB 2
DIN 51 502 : KP2K -25

The product is approved for KUBOTA machinery.

APPLICATIONS

KUBOTA GREASE EP 2 is a **multipurpose** grease, formulated for lubrication of loaded slide-ball, roller-bearings, wheel bearings, universal joints, chassis of **all KUBOTA machinery, operating in dusty, wet or dry conditions.** It is specifically developed for various shock loaded or vibrating applications.

Always avoid contamination of the grease by dust and/or dirt when applying.
Preferably use a pneumatic pump system or cartridges.

PERFORMANCES AND CUSTOMER BENEFITS

KUBOTA GREASE EP 2 has **excellent mechanical stability** and **good adhesion** to metal which allows **long working time** without product losses.

Its true multi-purpose character may replace a wide range of specific greases, allowing **stock rationalization** and simplified maintenance. KUBOTA GREASE EP 2 is miscible with most other conventional greases.

Its good thermal stability leads to **high resistance to temperature variations.**

KUBOTA GREASE EP 2 does not contain lead or other heavy metals considered harmful to human health and the environment.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

KUBOTA GREASE EP 2	METHOD	VALUE
NLGI Grade	-	2
Soap/Thickener	-	Lithium/Calcium
Colour	-	Sepia brown
Appearance	-	Smooth
Operating temperature range	°C	-25 to 130
Dropping point	°C	>190
Four ball weld load	daN	260/280

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification