



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

SDS # : 088168

**KUBOTA ENGINE OIL POWER
15W-40**

Date of the previous version: 2017-11-27

Revision Date: 2018-02-01

Version 1.01

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE
COMPANY/UNDERTAKING

1.1. Product identifier

Product name	KUBOTA ENGINE OIL POWER 15W-40
Number	G1F
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	TOTAL LUBRIFIANTS 562 Avenue du Parc de L'île 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71***
-----------------	--

For further information, please contact:

Contact Point	HSE***
E-mail Address	rm.msds-lubs@total.com***

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670
France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59
In France - Poison centers:
ANGERS : 02 41 48 21 21
BORDEAUX : 05 56 96 40 80
LILLE : 08 00 59 59 59
LYON : 04 72 11 69 11
MARSEILLE : 04 91 75 25 25
NANCY : 03 83 22 50 50
PARIS : 01 40 05 48 48
STRASBOURG : 03 88 37 37 37
TOULOUSE : 05 61 77 74 47

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

REGULATION (EC) No 1272/2008 ***

For the full text of the H-Statements mentioned in this Section, see Section 2.2. ***

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008***

2.2. Label elements**Labelled according to** REGULATION (EC) No 1272/2008*****Signal word**

None***

Hazard Statements ***

None***

Precautionary Statements

None***

Supplemental Hazard Statements

EUH210 - Safety data sheet available on request***

EUH208 - Contains Calcium long chain alkarylsulphonate . May produce an allergic reaction***

2.3. Other hazards**Physical-Chemical Properties** Contaminated surfaces will be extremely slippery.*****Environmental properties** The product may form an oil film on the water surface that may stop the oxygen exchange.***

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture*****Chemical nature**

Mineral oil of petroleum origin.***

Hazardous ingredients

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Reg. 1272/2008)
Amines,polyethylenepoly-,reaction products with 1,3-dioxolan-2-one and succinic anhydride monopolyisobutenyl derivs***	604-611-9***	no data available	147880-09-9	2.5-<5	Aquatic Chronic 4 (H413)
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and	272-238-5	01-2119657973-23	68784-31-6	1-<2.5	Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

1,3-dimethylbutyl) esters, zinc salts***					
Calcium long chain alkarylsulphonate ***	-	-	722503-69-7	1-<2.5	Skin Sens. 1 (H317) Aquatic Chronic 4 (H413)
Calcium long chain alkarylsulphonate***	-	-	722503-69-7	1-<2.5	Aquatic Chronic 4 (H413)
Calcium long chain alkaryl sulfonate***	-	-	722503-68-6	0.25-<1	Aquatic Chronic 4 (H413) Skin Sens.1 (H317)

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.***

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.***
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.***
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.***
Inhalation	Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.***
Ingestion	Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.***
Protection of First-aiders	First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.***

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Not classified based on available data. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required.***
Skin contact	Not classified based on available data. May produce an allergic reaction.***
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.***
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.***



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.***

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.***

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S. Phosphorous oxides. Nitrogen oxides (NO_x). Mercaptans. Zinc oxides. Silicon dioxide.***

5.3. Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.***

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.***

6.3. Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.***

Methods for cleaning up Dispose of contents/container in accordance with local regulation. In case of soil



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.***

6.4. Reference to other sections

Personal Protective Equipment	See Section 8 for more detail.
Waste treatment	See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling	For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.***
Prevention of fire and explosion	Take precautionary measures against static discharges.***
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.***

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.***
Materials to Avoid	Strong oxidizing agents.***

7.3. Specific end uses

Specific use(s)	Please refer to Technical Data Sheet for further information.***
------------------------	--

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m ³ , NIOSH (REL) TWA 5 mg/m ³ , STEL 10 mg/m ³ , ACGIH (TLV) TWA 5 mg/m ³ (highly refined)
Legend	See section 16



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

Derived No Effect Level (DNEL) ***

DNEL Worker (Industrial/Professional)***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts*** 68784-31-6			9.6 mg/kg bw/day (dermal) 6.6 mg/m ³ (inhalation)	

DNEL Consumer***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts*** 68784-31-6			4.8 mg/kg bw/day (dermal) 1.67 mg/m ³ (inhalation) 0.19 mg/kg bw/day (oral)	

Predicted No Effect Concentration (PNEC) ***

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts*** 68784-31-6	4 µg/l fw 4.6 µg/l mw 4.4 µg/l or	0.00701 mg/kg dw mw	0.0548 mg/kg dw		3.8 mg/l	8.33 mg/kg

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.***

Personal Protective Equipment

General Information

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.***

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.***



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

Eye Protection	If splashes are likely to occur, wear: Safety glasses with side-shields. EN 166.***
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.***
Hand Protection	Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.***

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance		limpid***	
Color		brown***	
Physical State @20°C		liquid***	
Odor		Characteristic***	
Odor Threshold		No information available***	
Property	Values	Remarks	Method
pH		Not applicable***	
Melting point/range		No information available***	
Boiling point/boiling range		No information available***	
Flash point ***	>*** 180*** °C*** >*** 356*** °F***		ASTM D 92*** ASTM D 92***
Evaporation rate		No information available***	
Flammability Limits in Air		***	
upper ***		No information available***	***
Lower ***		No information available***	***
Vapor Pressure		No information available***	
Vapor density		No information available***	
Relative density ***	*** 0.870*** - *** 0.890***	@ 15 °C***	ASTM D 1298***
Density	870*** - *** 890*** kg/m ³ ***	@ 15 °C***	ASTM D 1298***



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

Water solubility	Insoluble***		
Solubility in other solvents	No information available***		
logPow	No information available***		
Autoignition temperature	No information available***		
Decomposition temperature	No information available		
Viscosity, kinematic ***	*** 101*** mm2/s***	@ 40 °C***	ASTM D 445***
Explosive properties	Not explosive***		
Oxidizing Properties	Not applicable***		
Possibility of hazardous reactions	None under normal processing***		

9.2. Other information

Freezing Point No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information None under normal processing.***

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Reactions No dangerous reaction known under conditions of normal use.***

10.4. Conditions to avoid

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.***

10.5. Incompatible materials

Materials to Avoid Strong oxidizing agents.***

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Phosphorous oxides. Nitrogen oxides (NOx). Mercaptans. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S. Zinc oxides. Silicon dioxide.***

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

Acute toxicity Local effects Product Information

Skin contact	. Not classified based on available data. May produce an allergic reaction.***
Eye contact	. Not classified based on available data. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required.***
Inhalation	. Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.***
Ingestion	. Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.***
ATEmix (inhalation-dust/mist)	197.70*** mg/l***
ATEmix (inhalation-vapor)	779.10*** mg/l***

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts***	2900 mg/kg (rat)	> 5000 mg/kg (rabbit)	

Sensitization

Sensitization	Not classified based on available data. The supplier of one of the components contained within this formulation has indicated that they have data, which confirms that at the concentration used, no sensitisation classification is required . Contains sensitizer(s). May produce an allergic reaction.***
----------------------	--

Specific effects

Carcinogenicity	Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.***
Mutagenicity Germ Cell Mutagenicity	.*** Not classified based on available data.***
Reproductive toxicity	Not classified based on available data.***

Repeated Dose Toxicity

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure)	Not classified based on available data.***
Specific target organ systemic toxicity (repeated exposure)	Not classified based on available data.***



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

Aspiration toxicity Not classified based on available data.***

Other information

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).***

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified based on available data.***

Acute aquatic toxicity - Product Information***

No information available.***

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts*** 68784-31-6	EbL50 (72h) 240 mg/l Desmodesmus subspicatus ErL50 (0-72hr) 410 mg/L	EL50 (48h) 75 mg/l daphnia magna	LL50 (96h) 4.4 mg/l Oncorhynchus mykiss	

Chronic aquatic toxicity - Product Information

No information available.***

Chronic aquatic toxicity - Component Information

No information available.***

Effects on terrestrial organisms

No information available.***

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information No information available.***

logPow No information available***
Component Information No information available.***



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

12.4. Mobility in soil

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.***
Air	Loss by evaporation is limited.***
Water	The product is insoluble and floats on water.***

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.***

12.6. Other adverse effects

General Information No information available.***

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration.***
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.***
EWC Waste Disposal No.	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05.***
Other information	Refer to section 8 for safety and protective measures for disposal personnel.***

Section 14: TRANSPORT INFORMATION

<u>ADR/RID</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated
<u>ICAO/IATA</u>	Not regulated
<u>ADN</u>	Not regulated



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

No information available***

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available***

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H411 - Toxic to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life***

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water



SDS # : 088168

KUBOTA ENGINE OIL POWER 15W-40

Revision Date: 2018-02-01

Version 1.01

or = occasional release

Legend Section 8

TWA: Time Weight Average
 STEL: Short Time Exposure Limit
 PEL: Permissible exposure limit
 REL: Recommended exposure limit
 TLV: Threshold Limit Values

+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2018-02-01
 Revision Note: *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet